

INSTRUMENT COOLING FAN



SOURCE OF ENERGY



Millennium®



TAKING CARE
OF YOUR AIR



FITTED WITH

POWERFUL ROTOR

FOR ALL ROUND COOLING



QR Code Scan for
Visit our Website





Cooling Fan 4"



Cooling Fan 6"



Cooling Fan 8"






Cat No.	Type	Impeller Dia	Fan Size	Current Amp	Power (watts)	Speed RPM	Air Flow CFM	Noise db	Weight gm app
MDCF4S	Square	100mm/4"	120x120x38	0.13	22	2300	85	43	600
MDCF6RS	Round	150mm/6"	170x53	0.15	23	2300	180	52	1000
MDCF6SS	Square	150mm/6"	170x170x53	0.15	23	2300	180	52	1000
MDCF8SS	Round	200mm/8"	220x60	0.32	55	2300	360	56	1350
MDCF8SS	Square	200mm/8"	220x220x60	0.32	55	2300	360	56	1350

SUPPLY : 230V / 1 PH / AC / 50Hz | Current, Power, Speed, CFM, db within tolerance $\pm 10\%$

Applications :

- Generally Used in System, panel box etc to keep the system cool and also used as exhaust fan.
- Suitable for Bathroom, Panels UPS, AC air circulation
- Choice of voltage : 220V / 110V / 24VAC
- Impeller of high quality PCT+30% fibre UL 94V.O.
- High RPM delivers High CFM even at low power consumption
- Noiseless operation, Corrosion less body
- Impedance protected, Light in weight & sturdier function
- Motor Design : Shaded Pole, Motor Protection : Impedance Protected
- Housing : Aluminum Die - Cast, Insulation : Class B
- Insulation Resistance : Above 100M Ohms at 500 VDC
- Operating Temperature : 10 to 70°C for Sleeve Bearing

Finger Guard Mounting Size	Item Code	Surface Treatment	Suitable for Fan	Fan with Finger Guard
	MDCF4S	CHROME PLATING	120x120x38	
	MDCF6SS MDCF6SB	CHROME PLATING	170x170x53	
	MDCF6RS MDCF6RB	CHROME PLATING	170x53	
	MDCF8SS MDCF8SB	CHROME PLATING	220x220x60	
	MDCF8RB	CHROME PLATING	220x60	